

Angle Iron Trailers

5 X 8
2,000 Lbs.

5 X 10
3,000 Lbs.*

6 X 10
3,000 Lbs.*

6 X 12
3,000 Lbs.*

7 X 12
3,000 Lbs.*

7 x 16
7,000 Lbs.



*Actual GVWR listed on spec sheet.

Check out these other great features:

- EZ Lube Hubs
- Pressure Treated Decking
- True-Trac Alignment
- Square and Teardrop Fenders
- Heavy Duty Deck Screws
- Fully Factory Assembled
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping

Sure-Trac Angle Iron Trailers - These trailers are reliable, rugged and built for work. Our powder coated finish provides unmatched protection and exceptional good looks. They are fully assembled at the factory and ready for your toughest jobs. The unique gate is designed for ease of use and speed in operation.



Set-Back Tongue Jack - Clearance for tailgate and SUV rear doors. (Optional)



Fold Flat Tube Frame Ramp Gate
20% lighter and 40% stronger!



Protected Lights - ALL required DOT approved lights and reflectors.



Self-Retained Gate Pins - Fast, reliable and never lost.



Full Seam Welds - on all joints ensure structural integrity throughout the frame.



New Tires Wheels and Axles - Sure-Trac trailers have all new tires, wheels, and axles. In many states it is illegal to sell new trailers with used running gear.

Powder Coated Finish - All Sure-Trac trailers are powder coated for a durable high-gloss finish that will last for years.




Novae[®]
NovaeCorp.com

800-372-1755

ANGLE IRON TRAILER SPECIFICATIONS						
	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 16
GVWR	2000	2990				7000
GAWR	2000	3500				
Curb Weight	580	720	970	980	990	1760
Payload	1420	2270	2020	2010	2000	5240
Max Hitch Weight	200	300				700
Frame	3 x 2 x 3/16					3 x 2 x 1/4
Cross Members	3 x 2 x 3/16					
Top Rail	2 x 2 x 1/8					
Tongue	A-Frame 3" Channel					A-Frame 3" Channel
Uprights	2 x 2 x 1/8					
Coupler	2" Ball					2-5/16" Ball
Jack	Top Wind 2000#					
Fenders	Square Rolled with Back					Teardrop Rolled with Back
EZ-Lube Axles	Cambered Idler with Brake Flange					Cambered Brake & Idler
Suspension	Leaf Spring					Equalized Leaf Spring
Tires	175/80D13 LRC	205/75D15 LRC				
Wheels	13"	15"				
	White, Spoke or Modular					
Floor	2 X 6 Pressure Treated Pine					
Lights	DOT stop, Tail, Turn, and Marking			DOT stop, Tail, Turn, Marking and Clearance		
Electric Plug	4 Way Flat					7 Way Round
Finish	Powder Coated High Gloss Black					
Overall Length	137"	161"		185"		233"
Bed Length	96"	120"		144"		192"
Bed Width	62"		71.5"		81.5"	
Floor Height	16"	18"				
Coupler Height	14"	16"				
Gate	2 x 2 Tubing, Mesh Covered, Full Width Ramp Gate					
OPTIONS						
Wheel Upgrades	205/75D15 LRC	ST225/75D15 LRC				
Spare Tire Option	Matching Tire and Rim, Also Available - U-Bolt Carrier					
Brake Upgrades	Includes Breakaway Kit, 7 Way Plug, Brake Axle					Includes Second Brake Axle

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.