

## Steel Deck Car Hauler Trailers



Optional Removable Teardrop Fenders



|              |              |
|--------------|--------------|
| 7 x 18       | 7 x 20       |
| 7,000 Lbs.   | 7,000 Lbs.   |
| 10,000 Lbs.* | 10,000 Lbs.* |

\*Actual GVWR listed on spec sheet.

**Sure-Trac Car Hauler Trailers** – The frame is structural 5" tubing with heavy duty, 16 inch on center crossmembers. We offer MaxiStrength<sup>™</sup> stitch welded diamond plate steel decking. The air-dam bulkhead and D-Ring tie downs provide a smooth and secure ride. The engineered tailboard has sealed recessed lights. This trailer incorporates the best available construction, material and overall fit and finish.

**Check out these other great features:**

- EZ-Lube Hubs
- MaxiStrength<sup>™</sup> Welds
- True-Trac Alignment
- Conduit Protected Wiring
- Gel-Filled Connectors
- New Tires, Wheels and Axles
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



**Optional 7000 Lb Set-Back Tongue Jack** – Provides clearance for Tailgate and SUV Rear Doors.



**Slide In Ramps** – Heavy-duty, 5 ft. ramps and beavertail for low clearance vehicles.



**Ramp Compartments** – Ramps fit neatly under deck for fast loading and unloading.



**Stake Pockets & Rub Rail** – Full length on both sides.



**Teardrop Fenders** – With backers allow for a clean ride and smooth good looks.



**5K Lbs. D-Ring tie Downs** – At each corner provide easy load securement.



**Sealed Lights** – DOT approved lights and reflective tape.

**Powder Coated Finish** – All Sure-Trac trailers are powder coated for a durable high-gloss finish that will last for years.




**Novae<sup>®</sup>**  
NovaeCorp.com

**800-372-1755**

| STEEL DECK CAR HAULER TRAILERS SPECIFICATIONS |  |                           |                          |                           |
|---|--|---------------------------|--------------------------|---------------------------|
|   | 7000 Lb<br>7 X 18 Steel  | 9990 Lb<br>7 X 18 Steel   | 7000 Lb<br>7 X 20 Steel  | 9990 Lb<br>7 X 20 Steel   |
| <b>GVWR</b>                                   | 7000   | 9990                      | 7000                     | 9990                      |
| <b>GAWR</b>                                   | 3500   | 5000                      | 3500                     | 5000                      |
| <b>Curb Weight</b>                            | 1920   | 2140                      | 1920                     | 2140                      |
| <b>Payload</b>                                | 5080   | 7850                      | 5080                     | 7850                      |
| <b>Max Hitch Weight</b>                       | 700  | 1000                      | 700                      | 1000                      |
| <b>Frame</b>                                  | 5 Inch Tubing  |                           |                          |                           |
| <b>Cross Members</b>                          | 2 x 2 Tubing   | 3 x 2 Tubing              | 2 x 2 Tubing             | 3 x 2 Tubing              |
| <b>Tongue</b>                                 | 5 x 2 Full wrap Tubing   |                           |                          |                           |
| <b>Coupler</b>                                | 2" Ball  | 2-5/16" Ball              | 2" Ball                  | 2-5/16" Ball              |
| <b>Jack</b>                                   | 2000 Lb Top Wind   | 5000 Lb Top Wind          | 2000 Lb Top Wind         | 5000 Lb Top Wind          |
| <b>Fenders</b>                                | Teardrop   |                           |                          |                           |
| <b>Axles</b>                                  | Cambered Brake and Idler   | Cambered Brake Both Axles | Cambered Brake and Idler | Cambered Brake Both Axles |
| <b>Easy Lube Axle</b>                         | Greasable hubs on both axles                                     |                           |                          |                           |
| <b>Suspension</b>                             | Double Eye Leaf Spring   |                           |                          |                           |
| <b>Tires</b>                                  | 205/75D15 LRC  | 225/75D15 LRD             | 205/75D15 LRC            | 225/75D15 LRD             |
| <b>Wheels</b>                                 | 15 In, 5 on 4.5  | 15 In, 6 on 5.5           | 15 In, 5 on 4.5          | 15 In, 6 on 5.5           |
|   | White, Spoke or Modular  |                           |                          |                           |
| <b>Floor</b>                                  | 1/8 Tread Plate  |                           |                          |                           |
| <b>Lights</b>                                 | Sealed DOT Stop, Tail and Turn, Clearance and Reflective Marking |                           |                          |                           |
| <b>Electric Plug</b>                          | 7 Way Round  |                           |                          |                           |
| <b>Finish</b>                                 | Powder Coated High Gloss Black                                   |                           |                          |                           |
| <b>Overall Length</b>                         | 22'  |                           | 24'                      |                           |
| <b>Bed Length Flat</b>                        | 14'  |                           | 16'                      |                           |
| <b>Drop Length</b>                            | 4'   |                           |                          |                           |
| <b>Bed Width</b>                              | 82"  |                           |                          |                           |
| <b>Floor Height</b>                           | 21-1/2"  | 23"                       | 21-1/2"                  | 23"                       |
| <b>Coupler Height</b>                         | 17"  | 18"                       | 17"                      | 18"                       |
| <b>Ramps</b>                                  | 5' Fabricated 10 Ga  | 5' Reinforced 10 Ga       | 5' Fabricated 10 Ga      | 5' Reinforced 10 Ga       |
| OPTIONS                                       |  |                           |                          |                           |
| <b>Spare Tire</b>                             | Matching Tire and Rim<br>Also Available U-Bolt Carrier           |                           |                          |                           |
| <b>Brake Axle</b>                             | Second Brake Axle  | N/A                       |                          |                           |
| <b>Jack</b>                                   | Heavy Duty, 7000 Lb Frame Welded Drop-leg Jack with Foot Plate   |                           |                          |                           |

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.