

## Tilt Bed Equipment Trailers



POWDER  
COATED  
**TOUGH<sup>™</sup>**



18 ft. Tilt Deck

18 ft. Tilt Plus 4 ft. Fixed Deck (shown in optional Construction Yellow).

7 X 18 + 4	7 X 18
10,000 Lbs.*	10,000 Lbs.*
12,000 Lbs.	12,000 Lbs.
14,000 Lbs.	14,000 Lbs.

\*Actual GVWR listed on spec sheet.

**Sure-Trac Tilt Bed Equipment Trailers** - Our Tilt Bed Equipment trailer is built to handle your most demanding work load. Our trailer has a gravity down bed nested securely inside an amazingly strong heavy duty 6 inch frame. This trailer allows an operator to load heavy and dangerous equipment without cumbersome ramps or gates. The bed is cushioned as it gently comes to rest using a hydraulic dampening cylinder. The cylinder is mounted to a heavy duty 3 x 3 x 1/4 inch tube for added strength and security. The pivot hinge has grease zerks for easy maintenance to provide a lifetime of trouble free smooth rotation. The loading Knife Edge deck plate is a heavy 5/16 tread plate with 1/4 inch gusset transition supports to support the heavy equipment this trailer is designed to carry.

### Check out these other great features:

- True-Trac<sup>™</sup> Alignment
- 12 GA Tread Plate Fenders
- Conduit Protected Wiring
- Gel-Filled Connectors
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



**Sealed Recessed Lights**  
- DOT approved lights and reflective tape.



**Optional Gooseneck Available**



**Full Seam Welds** - On all joints ensure structural integrity throughout the frame.



**HD 1/4" Stake Pockets**  
- and full-length rub rail.



**Optional 7000 lb. Drop-Leg-Jack** - This rugged design doubles as a spare tire mount.



**Single Driver's Side CamLoc<sup>™</sup> Release Lever**  
- Locks bed in place.



**New Tires, Wheels and Axles** - In many states it is illegal to sell new trailers with used running gear.



**Powder Coated Finish** - A durable high-gloss finish that will last for years.



**800-372-1755**

TILT BED EQUIPMENT TRAILERS SPECIFICATIONS			
	10K	12K	14K
GVWR	9990	12000	14000
GAWR	5200	6000	7000
Curb Weight 18	3080	3180	3210
18 + 4	3680	3780	3780
Payload 18	6910	8820	10790
18 + 4	6310	8220	10220
Max Hitch Weight	1000	1200	1400
Frame	6" C-Channel and Tubing		
Cross Members	3" C-Ch. (16 On-Ctr)		
Tongue	6" C-Channel		
Coupler	2 5/16 A-Frame		
Jack	Coupler Mounted Jack		
Fenders	HD Tread Plate		
Axles	Easy Lube Cambered Brake, 4" Drop		
Suspension	Eye to Eye Spring		
Tires	225/75D15 LRD (D) Bias	7.5-16 LRF Bias	235/80*16 LRE (R) Radial
Wheels	6 Lug on 5.5	8 Lug on 6.5	
	16 X 6K, White or Grey, Modular		
Floor	2X6 Treated Pine		
Lights	Rubber Mounted/Sealed DOT stop, Tail, Turn, Marking and Clearance		
Electric Plug	7 Way Round		
Finish	Powder Coated High Gloss		
Length (Overall/Bed) 18	23'9"/18.5		
18 + 4	27'9"/4' + 18.5'		
Between Fenders	81-1/4"		
Floor Height	20"		
Coupler Height	18"	20"	
OPTIONS			
	10K	12K	14K
Spare Tire	Matching Tire and Rim Also Available U-Bolt Carrier		
Ball Coupler	Pintle Eye or 2-5/16 Adjustable Ball		
Wheel Type	(R) Radial		N/A
Floor Upgrade	2X6 Oak		
Spring	Slipper Spring		
Hitch	Gooseneck Hitch		

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.